Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (previously presented) A motor, comprising:

a motor unit having first and second electrode terminals; and

a cylindrical case for covering and securing the motor unit, including a large case body having a cylindrical conductive portion which is directly electrically connected to the second electrode terminal, which is within the cylindrical case, and an insulating small case body out of which the first electrode terminal extends.

2. (original) The motor as claimed in claim 1, wherein the motor unit further comprises a commutator and contact springs, and the first and second electrode terminals of the motor are electrically connected to the commutator through the contact springs.

3. (original) The motor as claimed in claim 1, wherein the large case body and the insulating small case body comprise recess portions for connecting the large case body and the insulating small case body.

4. (currently amended) A motor, comprising:

a rotor ~~having~~electrically connected to first and second electrical terminals; and

a cylindrical case for covering and securing the rotor, including a cylindrical conductive portion electrically connected to the rotor and directly connected to the second electrical terminal ~~of the rotor~~, which second electrical terminal is within the cylindrical case, and an end case ~~electrically~~ connected to the rotor and out of which the first electrical terminal ~~of the rotor~~ extends.

5. (original) A motor, comprising:

a motor unit having first and second electrode terminals; and a cylindrical case for covering and securing the motor unit, including a large case body having a cylindrical conductive portion which is directly electrically connected to the second electrode terminal, and an insulating small case body directly provided with the first electrode terminal,

wherein the motor unit further includes a rotary shaft, a commutator and a contact spring, and the first electrode terminal extends through the insulating small case body and includes a first end which is electrically connected to the commutator through the contact spring, and a second end which is exposed on an exterior of the insulating small case body, to be connected to an external battery directly or through at least one conductive member.

6. (original) The motor as claimed in claim 5, wherein the second end of the first electrode terminal is turned to form a contact head.

7. (currently amended) A motor, comprising:

a rotor ~~having~~electrically connected to first and second electrical terminals; and

a cylindrical case for covering and securing the rotor, including a cylindrical conductive portion electrically connected to the rotor and directly connected to the second electrical terminal ~~of the rotor~~, and an end case ~~electrically~~ connected to the rotor and directly connected to the first electrical terminal ~~of the rotor~~,

wherein the rotor further comprises a rotary shaft, a commutator and a contact spring, and the first electrical terminal extends through the end case and includes a first end which is electrically connected to the commutator ~~trough~~through the contact spring, and a second end which is exposed on an exterior of the end case to be connected to an external battery directly or through at least one conductive member.

8. (original) The motor as claimed in claim 7, wherein the second end of the first electrical terminal is turned to form a contact head.

9. (original) A motor, comprising:

a motor unit having first and second electrode terminals; and

a cylindrical case for covering and securing the motor unit, including a large case body having a cylindrical conductive portion which is directly electrically connected to the second electrode terminal, and an insulating small case body directly provided with the first electrode terminal, wherein one of the first electrode terminal of the motor and the cylindrical conductive portion of the large case body is electrically connected to a first electrode of the battery, and the other of the first electrode and the cylindrical conductive portion is conductively connected to a second electrode of the battery.

10. (original) The motor as claimed in claim 9, wherein the motor unit further comprises a commutator and contact springs, and the first and second electrode terminals of the motor are electrically connected to the commutator through the contact springs.

11. (currently amended) A motor, comprising:

a rotor ~~having~~electrically connected to first and second electrical terminals; and

a cylindrical case for covering and securing the rotor, including a cylindrical conductive portion electrically connected to the rotor and directly connected to the second electrical terminal ~~of the rotor~~, and an end case~~ electrically~~ connected to the rotor and directly connected to the first electrical terminal~~ of the rotor~~,

wherein one of the first electrode terminal~~ of the rotor~~ and the cylindrical conductive portion of the large case body is electrically connected to a first electrode of the battery, and the other of the first electrode and the cylindrical conductive portion is conductively connected to a second electrode of the battery.

12. (previously presented) A motor, comprising:

a motor unit having first and second electrode terminals; and

a cylindrical case for covering and securing the motor unit, including a large case body having a cylindrical conductive portion which is directly electrically connected to the second electrode terminal, and an insulating small case body directly provided with the first electrode terminal,

wherein the motor unit further includes a rotary shaft, a commutator and a contact spring, and the first electrode terminal passes through the insulating small case body in an approximately parallel direction to the rotary shaft, at a distance from the rotary shaft, and includes a first end which is electrically connected to the commutator through the contact spring, and a second end which projects outwardly from the insulating small case body to connect to an external battery directly or through a conductive member.

13. (previously presented) The motor as claimed in claim 12, wherein the second end of the first electrode terminal is turned to form a contact head.

14. (currently amended) A motor, comprising:

a rotor ~~having~~electrically connected to first and second electrical terminals; and

a cylindrical case for covering and securing the rotor, including a cylindrical conductive portion electrically connected to the rotor and directly connected to the second electrical terminal ~~of the rotor~~, and an end case~~-electrically~~ connected to the rotor and directly connected to the first electrical terminal~~-of the rotor~~,

wherein the rotor further comprises a rotary shaft, a commutator and a contact spring, and the first electrical terminal passes through the end case in an approximately parallel direction to the rotary shaft, at a distance from the rotary shaft, and includes a first end which is electrically connected to the commutator trough the contact spring, and a second end which projects outwardly from the end case to be adapted to connect to an external battery directly or through a conductive member.

15. (previously presented) The motor as claimed in claim 14, wherein the second end of the first electrical terminal is turned to form a contact head.

16. (previously presented) A motor, comprising:

a motor unit having first and second electrode terminals and a rotary shaft; and

a cylindrical case for covering and securing the motor unit, including a large case body having a cylindrical conductive portion which is directly electrically connected to the second electrode terminal, and an insulating small case body directly provided with the first electrode terminal,

wherein the first electrode terminal passes through the insulating small case body in an approximately parallel direction to the rotary shaft, and includes an end which projects outwardly from the insulating case body to be connected to an electric power source.

17. (previously presented) The motor as claimed in claim 16, wherein the motor unit further comprises a commutator and contact springs, and the first and second electrode terminals of the motor are electrically connected to the commutator through the contact springs.

18. (previously presented) The motor as claimed in claim 16, wherein the large case body and the insulating small case body comprise recess portions for connecting the large case body and the insulating small case body.

19. (currently amended) A motor, comprising:

a rotor ~~having~~electrically connected to first and second electrical terminals and having a rotary shaft; and

a cylindrical case for covering and securing the rotor, including a cylindrical conductive portion electrically connected to the rotor and directly connected to the second electrical terminal ~~of the rotor~~, and an end case~~ electrically~~ connected to the rotor and directly connected to the first electrical terminal~~ of the rotor~~,

wherein the first electrode terminal passes through the~~ insulating small~~end case body in an approximately parallel direction to the rotary shaft, and includes an end which projects outwardly from the~~ insulating~~end case~~ body~~ to be connected to an electric power source.

20. (previously presented) The motor as recited in claim 16, wherein the end which projects is turned to form a contact head.

21. (previously presented) The motor as recited in claim 19, wherein the end which projects is turned to form a contact head.

22. (previously presented) The motor as recited in claim 1, wherein the first electrode connects to an electric power source through a conductive member.

23. (previously presented) The motor as recited in claim 1, wherein the second electrode connects to an electric power source through one of directly and at least one conductive member.

24. (previously presented) The motor as recited in claim 4, wherein the first electrode connects to an electric power source through a conductive member.

25. (previously presented) The motor as recited in claim 4, wherein the second electrode connects to an electric power source through one of directly and at least one conductive member.

26. (previously presented) The motor as recited in claim 5, wherein the second electrode connects to the external battery through one of directly and at least one conductive member.

27. (previously presented) The motor as recited in claim 7, wherein the second electrode connects to the external battery through one of directly and at least one conductive member.

28. (previously presented) The motor as recited in claim 12, wherein the second electrode connects to the external battery through one of directly and at least one conductive member.

29. (previously presented) The motor as recited in claim 14, wherein the second electrode connects to the external battery through one of directly and at least one conductive member.

30. (previously presented) The motor as recited in claim 16, wherein the second electrode connects to the electric power source through one of directly and at least one conductive member.

31. (previously presented) The motor as recited in claim 19, wherein the second electrode connects to the electric power source through one of directly and at least one conductive member.